Material Safety Data Sheet

SANTOLUBES LLC

SANTOTRAC, SANTOVAC, SANTOLUBES, AND SYNERGY P.O. Box 960 St. Charles, MO 63302-0960

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SANTOVAC OS-124™ POLYPHENYL ETHER LUBRICANT

Chemical Family: Polyphenyl ether

FOR CHEMICAL EMERGENCY, SPILL LEAK, FIRE, EXPOSURE, OR ACCIDENT

Call CHEMTREC - Day or Night - 1-800-424-9300.

For additional non-emergency information, call: 636-723-0240

2. COMPOSITION/INFORMATION ON INGREDIENTS

Five-ring polyphenyl ether, CAS Number for this material is 2455-71-2.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

NO SIGNIFICANT HAZARDS ASSOCIATED WITH THIS MATERIAL

<u>POTENTIAL HEALTH EFFECTS</u> It is not a hazardous chemical(s) under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Likely Routes of Exposure: skin contact

Occupational exposure to this material has not been reported to cause significant adverse health effects. On the basis of available information, exposure to OS-124TM polyphenyl ether lubricant is not expected to produce significant adverse human health effects when recommended safety precautions are followed.

Refer to Section 11 for toxicological Information.

4. FIRST AID MEASURES

IF IN EYES OR ON SKIN, Immediate first aid is not likely to be required. However, this material can be removed by washing thoroughly with soap and water. Wash heavily contaminated clothing before reuse.

IF INHALED, immediate first aid is not likely to be required. However, if symptoms occur, remove to fresh air. Remove material from eyes, skin and clothing.

IF SWALLOWED, immediate first aid is not likely to be required. A physician or Poison Control Center can be contacted for advice.

5. FIRE FIGHTING MEASURES

Extinguishing Media: In case of fire, use water spray (fog), foam, dry chemical, or CO₂.

SANTOVAC® OS-124

Unusual Fire and Explosion Hazards: None known

Fire Fighting Equipment: Fire fighters and others exposed to products of combustion should wear self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

6. ACCIDENTAL RELEASE MEASURES

Contain large spills with dikes and transfer the material to appropriate containers for reclamation or disposal. Absorb remaining material or small spills with an inert material and then place in a chemical waste container. Flush residual spill area with water.

Refer to Section 13 for disposal information and Section 15 for reportable quantity information.

7. HANDLING AND STORAGE

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF MATERIAL FROM EYES, SKIN AND CLOTHING.

Emptied container retains vapor and product residue. Observe all labeled safeguards until container is cleaned, reconditioned, or destroyed.

Storage: Product is stable under normal conditions of storage and handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: This product does not cause significant eye irritation or eye toxicity requiring special protection. Use good industrial practice to avoid eye contact.

Skin Protection: Although it does not present a significant skin concern, minimize skin contamination by following good industrial practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after handling.

Respiratory Protection: Avoid breathing mist. Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure is excessive. Consult respirator manufacturer to determine appropriate type equipment for given application. Observe respirator use limitations specified by NIOSH/MSHA or the manufacturer. Respiratory protection programs must comply with 29 CFR 1910.134.

Ventilation: Provide natural or mechanical ventilation to minimize exposure. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Airborne Exposure Limits:

Product: OS-124[™] Polyphenyl Ether Lubricant

OSHA PEL: None established ACGIH TLV: None established

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Light yellow essentially clear liquid

Odor: Odorless to slight phenolic

Boiling Point: 889°F (476°C) @ 760 mm Hg

Material Safety Data Sheet SANTOVAC® OS-124

Pour Point: 40°F

Specific Gravity: 1.195 - 1.201 @ 25/25°C

pH: Neutral

Vapor Density: 15.5 (air = 1)

Solubility: Soluble in acetone and light aromatic solvents; insoluble in water

NOTE: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

10. STABILITY AND REACTIVITY

Stability: Product is stable under normal storage and handling conditions.

Materials to Avoid: Exposure to materials that are highly oxidizing should be avoided.

Hazardous Decomposition Products: Continued use at temperatures above 425 °C may result in the formation of benzene and phenol. If the product is burned, complete combustion produces carbon dioxide and water and partial combustion produces carbon monoxide, smoke, soot and low molecular weight hydrocarbons.

Hazardous Polymerization: Does not occur.

11. TOXICOLOGICAL INFORMATION

Data from laboratory studies with OS-124TM polyphenyl ether lubricant are summarized as follows:

Single exposure (acute) studies indicate:

Oral - Practically Nontoxic (Rat LD50 > 34,600 mg/kg)

Oral - Practically Nontoxic (Rabbit LD50 > 34,600 mg/kg)

Dermal - Practically Nontoxic (Rabbit LD50 > 34,600 mg/kg)

Inhalation - Practically Nontoxic (Rat 4-hr LC50 > 47 mg/l. No deaths and no signs of toxicity

were observed in animals exposed to 47 mg/l, the highest

atmospheric

concentration achievable by heating the material to 329°C in

this study.)

12. ECOLOGICAL INFORMATION

SANTOLUBES LLC has not conducted environmental toxicity studies with this product.

13. DISPOSAL CONSIDERATIONS

This material when discarded is not a hazardous waste as defined by the Resource, Conservation and Recovery Act (RCRA), 40 CFR 261. Dispose of in accordance with all federal, state and local environmental regulations. Recommended method of disposal is by high temperature incineration at a RCRA approved TSDF. If there are any questions regarding the disposal of this material, please consult the Environmental, Health & Safety Department of SANTOLUBES LLC.

14. TRANSPORT INFORMATION

The data provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transportation.

This product is not hazardous under the applicable DOT, ICAO/IATA, or IMDG regulations.

15. REGULATORY INFORMATION

TSCA Inventory: All components are listed.

SARA Hazard Notification


Hazard Categories Under Title III Rules (40 CFR 370): Not Applicable

Section 313 Toxic Chemical(s): Not Applicable

CERCLA Reportable Quantity: Not Applicable

16. OTHER INFORMATION

This is for people trained in the <u>National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System</u> (HMIS) and the <u>National Fire Protection Association</u> (NFPA 704):



HAZARD INDEX

0 = Minimal Hazard 1 = Slight Hazard	2 = Moderate Hazard	3 = Serious Hazard	4 = Severe Hazard
--------------------------------------	---------------------	--------------------	-------------------

SANTOVAC® is a trademark of SANTOLUBES LLC.

NOTICE: Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, SANTOLUBES LLC makes no representations as to the completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving same will make their own determinations as to its suitability for their purposes prior to use. In no event will SANTOLUBES LLC be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OR MERCHANTABILITY, FITNESS FOR A

Page 5 of 5

PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

Date 06/17/09 Supersedes 03/14/08